

Floor Care | Heavy-Duty Actuators

ZZQ-TG 08

The ZZQ-TG 08 actuator is a powerful actuator specially designed for heavy duty floor machine such as big brush pad lift up and down. Optional Voltage 24/36VDC and Stroke, Max Load Capacity 6000N and Moving Speed: 25mm/s.



THIS ACTUATOR IS A POWERFUL ACTUATOR SPECIALLY DESIGNED FOR HAVEY DUTY PURPOSES SUCH AS BIG BRUSH PAD LIFT UP AND DOWN.

ZZQ-TG08-24-20-114

Rated Power (W): 24.5
Rated Voltage (V): 24V
Gear Ratio: 20:1
Stroke Length (mm): 114
Moving Speed (mm/s): 9~12
Force (N): 2700N in Push and Pull
Installation Dimension (mm): 350
Protection Class: IP54
Life: ≥50000 Cycles
Duty Cycle: S3-10%



THIS ACTUATOR IS A POWERFUL ACTUATOR SPECIALLY DESIGNED FOR HAVEY DUTY PURPOSES SUCH AS BIG BRUSH PAD LIFT UP AND DOWN.

ZZQ-TG08-36-20-36

Rated Power (W): 24.5
Rated Voltage (V): 36V
Gear Ratio: 20:1
Stroke Length (mm): 36
Moving Speed (mm/s): 9~11
Force (N): 2700N in Push and Pull
Protection Class: IP54
Life: ≥50000 Cycles
Duty Cycle: S3-10%



THIS ACTUATOR IS A POWERFUL ACTUATOR SPECIALLY DESIGNED FOR HAVEY DUTY PURPOSES SUCH AS BIG BRUSH PAD LIFT UP AND DOWN.

ZZQ-TG08-36-22-89

Rated Power (W): 8.5
Rated Voltage (V): 36V
Gear Ratio: 22:1
Stroke Length (mm): 89
Moving Speed (mm/s): 9~10.5
Force (N): 910N in Push and Pull
Installation Dimension (mm): 139
Protection Class: IP54
Life: ≥60000 Cycles
Duty Cycle: S3-10%



THIS ACTUATOR IS A POWERFUL ACTUATOR SPECIALLY DESIGNED FOR HAVEY DUTY PURPOSES SUCH AS BIG BRUSH PAD LIFT UP AND DOWN.

ZZQ-TG08-36-20-110

Rated Power (W): 24.5
Rated Voltage (V): 36V
Gear Ratio: 20:1
Stroke Length (mm): 110
Moving Speed (mm/s): 9~12
Force (N): 2700N in Push and Pull
Installation Dimension (mm): 310
Protection Class: IP54
Life: ≥50000 Cycles
Duty Cycle: S3-10%



THE ACTUATOR IS A POWERFUL ACTUATOR SPECIALLY DESIGNED FOR HAVEY DUTY PURPOSES SUCH AS BIG BRUSH PAD LIFT UP AND DOWN.

ZZQ-TG08-36-20-152A

Rated Power (W): 24.5
Rated Voltage (V): 36V
Gear Ratio: 22:1
Stroke Length (mm): 152
Moving Speed (mm/s): 9~11
Force (N): 1700N in Push and Pull
Installation Dimension (mm): 320
Protection Class: IP54
Life: ≥50000 Cycles
Duty Cycle: S3-10%