

Intelligent Office and Home furniture line

Lifting columns for the Electric Sit-Stand Table

LIFTING COLUMNS HEAVY-DUTY



PRODUCT MODEL: ZZQ-LZ01-J2 (CIRCULAR)
 Thrust: Max 800N/180 lbs per leg
 Speed: 38mm/s, 1.5"/s
 Installation Dimension: 685mm/28" (Std)
 Stroke length: 500mm/20" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS



PRODUCT MODEL: ZZQ-LZ01-J3 (CIRCULAR)
 Thrust: Max 800N/180 lbs per leg
 Speed: 38mm/s, 1.5"/s
 Installation Dimension: 580mm/23" (Std)
 Stroke Length: 650mm/26" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS



PRODUCT MODEL: ZZQ-LZ02-J2 (RECTANGULAR)
 Thrust: Max 800N/180 lbs per leg
 Speed: 38mm/s, 1.5"/s
 Installation Dimension: 685mm/28" (Std)
 Stroke Length: 500mm/20" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS



PRODUCT MODEL: ZZQ-LZ02-J3 (RECTANGULAR)
 Thrust: Max 800N/180 lbs per leg
 Speed: 38mm/s, 1.5"/s
 Installation Dimension: 580mm/23" (Std)
 Stroke Length: 650mm/26" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS



PRODUCT MODEL: ZZQ-LZ04-J2 (SQUARE)
 Thrust: Max 800N/180 lbs per leg
 Speed: 38mm/s, 1.5"/s
 Installation Dimension: 685mm/28" (Std)
 Stroke Length: 500mm/20" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS



PRODUCT MODEL: ZZQ-LZ04-J3 (SQUARE)
 Thrust: Max 800N/180 lbs per leg
 Speed: 38mm/s, 1.5"/s
 Installation Dimension: 580mm/23" (Std)
 Stroke Length: 650mm/26" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS

LIFTING COLUMNS LIGHT-DUTY



PRODUCT MODEL: ZZQ-LZ11-J2 (CIRCULAR)
 Thrust: Max 130 lbs per leg
 Speed: 32mm/s, 1.3"/s
 Installation Dimension: 685mm/28" (Std)
 Stroke length: 500mm/20" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS



PRODUCT MODEL: ZZQ-LZ14-J3 (CIRCULAR)
 Thrust: Max 130 lbs per leg
 Speed: 32mm/s, 1.3"/s
 Installation Dimension: 580mm/23" (Std)
 Stroke Length: 650mm/26" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS



PRODUCT MODEL: ZZQ-LZ08-J2 (RECTANGULAR)
 Thrust: Max 130 lbs per leg
 Speed: 32mm/s, 1.3"/s
 Installation Dimension: 685mm/28" (Std)
 Stroke Length: 500mm/20" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS



PRODUCT MODEL: ZZQ-LZ13-J3 (RECTANGULAR)
 Thrust: Max 130 lbs per leg
 Speed: 32mm/s, 1.3"/s
 Installation Dimension: 580mm/23" (Std)
 Stroke Length: 650mm/26" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS



PRODUCT MODEL: ZZQ-LZ12-J2 (SQUARE)
 Thrust: Max 130 lbs per leg
 Speed: 32mm/s, 1.3"/s
 Installation Dimension: 685mm/28" (Std)
 Stroke Length: 500mm/20" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS



PRODUCT MODEL: ZZQ-LZ15-J3 (SQUARE)
 Thrust: Max 130 lbs per leg
 Speed: 32mm/s, 1.3"/s
 Installation Dimension: 580mm/23" (Std)
 Stroke Length: 650mm/26" (Std)
 Motor Cable Length: 100cm/39.4", 200cm/78.7", 250cm/98.4"
 Cable Material: PVC or Non-PVC
 Duty Cycle: 10%
 Ambient Temperature: +5°C to +40 /41°F to 104°F
 Certificate: ETL & CE

COLORS